

# Enduro model



E15DMHL

## E9.9D

## E15D

### MODEL CODE (Approved code)

E9.9D 6B3 (6B3K)

E15D 6B4 (6B4K)

### MODELS AVAILABLE

E9.9D MH

E15D MH

### Dimension

Overall length	878 mm (34.6 in)
Overall width	363 mm (14.3 in)
Overall height	S: 1062 mm (41.8 in), L: 1189 mm (46.8 in), X: 1331 mm (52.4 in)
Engine transom height	S: 441 mm (17.4 in), L: 568 mm (22.4 in), X: 710 mm (30.3 in)
Minimum distance	–
Steering angle	40 deg. each direction

### Dry weight

**E9.9D** 38 – 40 kg

**E15D** 38 – 41 kg

Performance	E9.9D	E15D
Max. prop shaft output	7.3 kW (9.9 ps)	11.0 kW (15 ps)
Full throttle operating range	4500 – 5500 r/min	
Idling speed	1000 – 1100 r/min	
Fuel consumption	6.9 L/h @5500 r/min	7.7 L/h @5500 r/min

### Engine

Engine type	In-line 2
Displacement	246 cm <sup>3</sup>
Bore × stroke	56.0 × 50.0 mm
Compression ratio	7.0 :1
Scavenging	Loop charge
Fuel induction system	1 carburetor
Lubrication system	Pre-mixed fuel and oil
Oil - fuel mixing ratio	50 :1
Engine oil capacity	—
Ignition system	CDI
Ignition timing	TDC – BTDC 30.0 deg.
Spark plug	B8HS-10
Alternator	80 W (optional)
Cooling system	Raw-water, thermostatically controlled
Exhaust system	Through propeller boss

### Bracket / Drive

Trim	4 positions
Shallow water drive	1 position
Gear shift	F-N-R
Gear ratio	2.08 (27/13)
Gear oil capacity	0.220 L
Propeller fitting	Spline
Propeller rotation	Clockwise
Shaft length	S, L <span style="float: right;">S, L, X</span>

Feature Table		E9.9D	E15D
Security	Start in gear protection	•	•
	Engine stop switch lanyard	•	•
Corrosion prevention	Chrome plated water pump housing	•	•
	Multiple anode	•	•
Power unit	Carburetor	•	•
	Gasoline	Regular	Regular
Convenience	Shallow water drive	•	•

Optional Accessory	E9.9D	E15D
Lighting coil	•	•
Portable fuel tank	•	•
Spark plug	•	•

Rigging Accessory	E9.9D	E15D
Propeller	J Series	J/J1
	Dual Thrust J Series	J

Consumes	E9.9D	E15D
Yamalube gear oil GL4	•	•